

### Features

- High current TRIAC
- Low thermal resistance with clip bonding
- High commutation capability
- BTA series UL1557 certified (File ref: 81734)
- Packages are RoHS (2002/95/EC) compliant


### Applications

- On/off function in static relays, heating regulation, induction motor starting circuits
- Phase control operations in light dimmers, motor speed controllers, and similar

### Description

Available in high power packages, the BTA/BTB40-41 series is suitable for general purpose AC switching.

The BTA series provides an insulated tab (rated at 2500 V rms).



**Table 1. Device summary**

| Symbol            | Parameter                         | BTA40 <sup>(1)</sup> | BTA41 <sup>(1)</sup> | BTB41       | Unit |
|-------------------|-----------------------------------|----------------------|----------------------|-------------|------|
| $I_{T(RMS)}$      | On-state rms current              | 40                   | 41                   | 41          | A    |
| $V_{DRM}/V_{RRM}$ | Repetitive peak off-state voltage | 600 and 800          | 600 and 800          | 600 and 800 | V    |
| $I_{GT}$          | Triggering gate current           | 50                   | 50                   | 50          | mA   |

1. Insulated package

# 1 Characteristics

**Table 2. Absolute maximum ratings**

| Symbol             | Parameter   |                               |                                   | Value                          | Unit                   |
|--------------------|---|-------------------------------|-----------------------------------|--------------------------------|------------------------|
| $I_{T(RMS)}$       | On-state rms current<br>(full sine wave)  | TOP3                          | $T_c = 95\text{ }^\circ\text{C}$  | 40                             | A                      |
|                    |   | RD91 / TOP ins.               | $T_c = 80\text{ }^\circ\text{C}$  |                                |                        |
| $I_{TSM}$          | Non repetitive surge peak on-state<br>current (full cycle, $T_j$ initial = $25\text{ }^\circ\text{C}$ ) | F = 50 Hz                     | t = 20 ms                         | 400                            | A                      |
|                    |   | F = 60 Hz                     | t = 16.7 ms                       | 420                            |                        |
| $I^2t$             | $I^2t$ Value for fusing   | $t_p = 10\text{ ms}$          |                                   | 1000                           | $\text{A}^2\text{s}$   |
| dl/dt              | Critical rate of rise of on-state current<br>$I_G = 2 \times I_{GT}$ , $t_r \leq 100\text{ ns}$         | F = 120 Hz                    | $T_j = 125\text{ }^\circ\text{C}$ | 50                             | $\text{A}/\mu\text{s}$ |
| $V_{DSM}/V_{RSM}$  | Non repetitive surge peak off-state<br>voltage  | $t_p = 10\text{ ms}$          | $T_j = 25\text{ }^\circ\text{C}$  | $V_{DSM}/V_{RSM} + 100$        | V                      |
| $I_{GM}$           | Peak gate current   | $t_p = 20\text{ }\mu\text{s}$ | $T_j = 125\text{ }^\circ\text{C}$ | 8                              | A                      |
| $P_{G(AV)}$        | Average gate power dissipation  |                               | $T_j = 125\text{ }^\circ\text{C}$ | 1                              | W                      |
| $T_{stg}$<br>$T_j$ | Storage junction temperature range<br>Operating junction temperature range                              |                               |                                   | - 40 to + 150<br>- 40 to + 125 | $^\circ\text{C}$       |

**Table 3. Electrical characteristics ( $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified)**

| Symbol            | Parameter  |                                   |                                   | Value | Unit                   |
|-------------------|--|-----------------------------------|-----------------------------------|-------|------------------------|
| $I_{GT}^{(1)}$    | $V_D = 12\text{ V}$ $R_L = 33\text{ }\Omega$                                 | I - II - III                      | MAX.                              | 50    | mA                     |
|                   |  | IV                                |                                   | 100   |                        |
| $V_{GT}$          |  | ALL                               | MAX.                              | 1.3   | V                      |
| $V_{GD}$          | $V_D = V_{DRM}$ $R_L = 3.3\text{ k}\Omega$ $T_j = 125\text{ }^\circ\text{C}$ | ALL                               | MIN.                              | 0.2   | V                      |
| $I_H^{(2)}$       | $I_T = 500\text{ mA}$  |                                   | MAX.                              | 80    | mA                     |
| $I_L$             | $I_G = 1.2 I_{GT}$   | I - III - IV                      | MAX.                              | 70    | mA                     |
|                   |  | II                                |                                   | 160   |                        |
| $dV/dt^{(2)}$     | $V_D = 67\% V_{DRM}$ gate open   | $T_j = 125\text{ }^\circ\text{C}$ | MIN.                              | 500   | $\text{V}/\mu\text{s}$ |
| $(dV/dt)_c^{(2)}$ | $(dl/dt)_c = 20\text{ A/ms}$   |                                   | $T_j = 125\text{ }^\circ\text{C}$ | MIN.  | $\text{V}/\mu\text{s}$ |

1. Minimum  $I_{GT}$  is guaranteed at 5% of  $I_{GT}$  max.
2. for both polarities of A2 referenced to A1

**Table 4. Static characteristics**


| Symbol                 | Test conditions                                 |                             | Value | Unit |               |
|------------------------|---|-----------------------------|-------|------|---------------|
| $V_T^{(1)}$            | $I_{TM} = 60\text{ A}$ $t_p = 380\ \mu\text{s}$ | $T_j = 25\ ^\circ\text{C}$  | MAX.  | 1.55 | V             |
| $V_{t0}^{(2)}$         | Threshold voltage                               | $T_j = 125\ ^\circ\text{C}$ | MAX.  | 0.85 | V             |
| $R_d^{(2)}$            | Dynamic resistance                              | $T_j = 125\ ^\circ\text{C}$ | MAX.  | 10   | m $\Omega$    |
| $I_{DRM}$<br>$I_{RRM}$ | $V_{DRM} = V_{RRM}$                             | $T_j = 25\ ^\circ\text{C}$  | MAX.  | 5    | $\mu\text{A}$ |
|                        |   | $T_j = 125\ ^\circ\text{C}$ |       | 5    | mA            |

1. Minimum  $I_{GT}$  is guaranteed at 5% of  $I_{GT}$  max.
2. for both polarities of A2 referenced to A1


**Table 5. Thermal resistance**

| Symbol        | Test conditions       |                                   | Value | Unit               |
|---------------|-----------------------|-----------------------------------|-------|--------------------|
| $R_{th(j-c)}$ | Junction to case (AC) | RD91 (insulated) / TOP3 insulated | 0.9   | $^\circ\text{C/W}$ |
|               |                       | TOP3                              | 0.6   |                    |
| $R_{th(j-a)}$ | Junction to ambient   | TOP3 / TOP3 insulated             | 50    | $^\circ\text{C/W}$ |


**Figure 1. Maximum power dissipation versus on-state rms current (full cycle)**



**Figure 2. On-state rms current versus case temperature (full cycle)**



**Figure 3. Relative variation of thermal impedance versus pulse duration**



**Figure 4. On-state characteristics (maximum values)**




Figure 5. Surge peak on-state current versus number of cycles




Figure 6. Non-repetitive surge peak on-state current for a sinusoidal pulse and corresponding value of I<sup>2</sup>t




Figure 7. Relative variation of gate trigger, holding and latching current versus junction temperature




Figure 8. Relative variation of critical rate of decrease of main current versus (dV/dt)c (typical values)






Figure 9. Relative variation of critical rate of decrease of main current versus (dV/dt)c



## 2 Ordering information scheme

Figure 10. Ordering information scheme



### 3 Package information

- Epoxy meets UL94, V0
- Lead-free packages

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

**Table 6. TOP3 insulated and non-insulated dimensions**

| Ref. | Dimensions  |       |            |       |
|------|-------------|-------|------------|-------|
|      | Millimeters |       | Inches     |       |
|      | Min.        | Max.  | Min.       | Max.  |
| A    | 4.4         | 4.6   | 0.173      | 0.181 |
| B    | 1.45        | 1.55  | 0.057      | 0.061 |
| C    | 14.35       | 15.60 | 0.565      | 0.614 |
| D    | 0.5         | 0.7   | 0.020      | 0.028 |
| E    | 2.7         | 2.9   | 0.106      | 0.114 |
| F    | 15.8        | 16.5  | 0.622      | 0.650 |
| G    | 20.4        | 21.1  | 0.815      | 0.831 |
| H    | 15.1        | 15.5  | 0.594      | 0.610 |
| J    | 5.4         | 5.65  | 0.213      | 0.222 |
| K    | 3.4         | 3.65  | 0.134      | 0.144 |
| ØL   | 4.08        | 4.17  | 0.161      | 0.164 |
| P    | 1.20        | 1.40  | 0.047      | 0.055 |
| R    | 4.60 typ.   |       | 0.181 typ. |       |




Table 7. RD91 dimensions

| Ref. | Dimensions  |       |        |       |
|------|-------------|-------|--------|-------|
|      | Millimeters |       | Inches |       |
|      | Min.        | Max.  | Min.   | Max.  |
| A    | -           | 40.00 | -      | 1.575 |
| A1   | 29.90       | 30.30 | 1.177  | 1.193 |
| A2   | -           | 22.00 | -      | 0.867 |
| B    | -           | 27.00 | -      | 1.063 |
| B1   | 13.50       | 16.50 | 0.531  | 0.650 |
| B2   | -           | 24.00 | -      | 0.945 |
| C    | -           | 14.00 | -      | 0.551 |
| C1   | -           | 3.50  | -      | 0.138 |
| C2   | 1.95        | 3.00  | 0.077  | 0.118 |
| E3   | 0.70        | 0.90  | 0.027  | 0.035 |
| F    | 4.00        | 4.50  | 0.157  | 0.177 |
| I    | 11.20       | 13.60 | 0.441  | 0.535 |
| L1   | 3.10        | 3.50  | 0.122  | 0.138 |
| L2   | 1.70        | 1.90  | 0.067  | 0.075 |
| N1   | 33°         | 43°   | 33°    | 43°   |
| N2   | 28°         | 38°   | 28°    | 38°   |

## 4 Ordering information

**Table 8. Ordering information**

| Order code <sup>(1)</sup> | Marking   | Package   | Weight | Base qty | Delivery mode |
|---------------------------|-----------|-----------|--------|----------|---------------|
| BTA40-xxxB                | BTA40xxxB | RD91      | 20 g   | 25       | Bulk          |
| BTA41-xxxBRG              | BTA41xxxB | TOP3 Ins. | 4.5 g  | 30       | Tube          |
| BTB41-xxxBRG              | BTB41xxxB | TOP3      | 4.5 g  | 30       | Tube          |

1. xxx = voltage

## 5 Revision history

**Table 9. Document revision history**

| Date        | Revision | Changes   |
|-------------|----------|---|
| Sep-2003    | 5        | Last update.  |
| 25-Mar-2005 | 6        | TOP3 delivery mode changed from bulk to tube.   |
| 14-Oct-2005 | 7        | T <sub>c</sub> values for I <sub>T</sub> changed in Table 3. ECOPACK statement added.   |
| 10-Aug-2009 | 8        | Updated <a href="#">Table 2</a> to correctly place packages. Updated <a href="#">Figure 2</a> . <a href="#">Table 5</a> changed to correctly place TOP3. Updated ECOPACK statement. |



**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)