

## Specification

Model	Capacity (kVA)	Phase	Frequency (Hz)	Input voltage (V)	Output voltage (V)	Max. output current (A)	Shape
TDGC2,TDGC-0.2/0.5(M)	0.2	1	50/60	110/ 220	0-250	0.36/0.8	Round
TDGC2,TDGC-0.25/0.5(M)	0.25					0.4/1	
TDGC2,TDGC-0.5/0.5(M)	0.5					0.88/2	
TDGC2,TDGC-0.5(C)	0.5					0.88/2	
TDGC2,TDGC-1/0.5	1					1.6/4	
TDGC2,TDGC-2	2					3.2/8	Hexagon
TDGC2,TDGC-3/0.5	3					4.8/12	
TDGC2,TDGC-5/0.5	5					8/20	Round
TDGC2,TDGC-10/0.5	10					16/40	Octagon
TDGC2,TDGC-15/0.5	15					24/60	
TDGC2,TDGC-20/0.5	20	80					
TSGC2,TSGC-3/0.5	3	3	50/60	220/ 380	0-430	1.6/4	Hexagon
TSGC2,TSGC-6/0.5	6					3.2/8	
TSGC2,TSGC-10/0.5	10					5.4/13.4	Octagon
TSGC2,TSGC-15/0.5(M)	15					20	
TSGC2,TSGC-20/0.5(M)	20					28	
TSGC2,TSGC-30/0.5(M)	30					40	

Model		Dimmension(mm)								Weight Kg	
		L2	L1	H	H1	h	φ	d	D		R
TDGC2	-0.2	130	115	125	90	23	100	4	8		2.2
	-0.5	150	132	136	98	23	116	4	8		3.5
	-1	207	182	158	120	30	156	5	12		6.1
	-2	207	822	190	140	30	156	5	12		8.3
	-3	235	210	198	140	36	190	6	12		11
	-4	272	245	248	182	36	218	8	16		13.5
	-5	300	245	248	182	36	218	8	16		15.5
	-10	350	320	262	192	36	290	8	16		27
TSGC2	-3	207	182	450	396	30		8	12	92	19
	-6	240	182	558	490	30		8	12	92	26
	-9	270	210	567	490	36		8	12	112	33
	-15	305	245	681	616	36		10	16	131	49