



Products Industries Resources About TE Support Center My Account

Home > Products > PolySwitch Resettable Devices > Product Feature Selector > Product Details

NANOSMDC110F-2 Product Details

🚨 Share



■ Email



PolySwitch Resettable Devices

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Surface Mount Application
- Vmax Operating = 6 V
- Vmax = 6 V
- Imax = 100 A
- Family Name = nanoSMD

<u>View all Features</u>

Quick Links

- Check Pricing & Availability
- Search for Tooling
- Product Feature Selector Contact Us About This Product

NANOSMDC110F-2

(RF1359-000)

TE Internal Number: RF1359-000



🕒 Add to My Part List 🛮 🧺 Request Sample of Find Similar Products of Buy Product







Documentation & Additional Information

Product Drawings:

Catalog Pages/Data Sheets:

CP CATALOG 2011 - SURFACE-MOUNT (PDF, English)

Product Specifications:

nanoSMDC110F, 1 LAYER PANEL (PDF, English)

Application Specifications:

None Available

Instruction Sheets:

None Available

CAD Files:

None Available

Additional Information:

Product Line Information

Related Products:

Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- UL File Number = E74889
- CSA File Number = CA78165

Electrical Characteristics:

- Vmax Operating (V) = 6 Vmax (V) = 6
- Imax (A) = 100
- IH (Room Temperature) (A) = 1.1
- IT (Room Temperature) (A) = 2.20
- Rmin (Ω) = 0.07
- $R1 \operatorname{Max} [\operatorname{Post} \operatorname{Trip}] (\Omega) = 0.20$
- Power Dissipation (Max) (W) = 0.8

Termination Features:

Construction = Surface Mount

Contact Features:

Family Name = nanoSMD

Configuration Features:

- Form Factor (inches) = 1206
- <u>Form Factor (mm)</u> = 3216

Industry Standards:

List all Documents

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant
- TUV Certificate No. = R72041439

Environmental:

Operating Temperature (Max.) (°C) = 85

Operation/Application:

Application = Surface Mount

Packaging Features:

Packaging Method = Tape & Reel

Other:

Brand = Ravchem

Corporate Information

Who We Are Investors News Room Supplier Portal Careers

Ouick Links

Check Distributor Inventory Cross Reference Find Documents & Drawings Product Compliance Support Center Site Map

Customer Support

Email or Chat With Us Find a Phone Number Search Knowledge Base Manage your Account

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address











